

Q25_2.3.2 epp create command example

```
C: <?xml version="1.0" encoding="UTF-8" standalone="no"?>
C: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
C:   <command>
C:     <create>
C:       <domain: create>
C:         xml ns: domain="urn:ietf:params:xml:ns:domain-1.0">
C:           <domain: name>test-dn-0001.tld</domain: name>
C:           <domain: period unit="y">1</domain: period>
C:           <domain: ns>
C:             <domain: hostObj>ns1.hostexample.tld</domain: hostObj>
C:             <domain: hostObj>ns2.hostexample.tld</domain: hostObj>
C:           </domain: ns>
C:           <domain: registrant>MM4567</domain: registrant>
C:           <domain: contact type="admin">NFC1</domain: contact>
C:           <domain: contact type="tech">NFC1</domain: contact>
C:           <domain: contact type="tech">VIL1666</domain: contact>
C:           <domain: authInfo>
C:             <domain: pw>mypassword</domain: pw>
C:           </domain: authInfo>
C:         </domain: create>
C:       </create>
C:     <clTRID>a-client-reference</clTRID>
C:   </command>
C: </epp>
```

```
S: <?xml version="1.0" encoding="UTF-8" standalone="no"?>
S: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
S:   <response>
S:     <result code="1000">
S:       <msg>Command completed successfully</msg>
S:     </result>
S:     <resData>
S:       <domain: creData>
S:         xml ns: domain="urn:ietf:params:xml:ns:domain-1.0">
S:           <domain: name>test-dn-0001.tld</domain: name>
S:           <domain: crDate>2012-01-11T03:05:05.0Z</domain: crDate>
S:           <domain: exDate>2013-01-11T03:05:05.0Z</domain: exDate>
S:         </domain: creData>
S:       </resData>
S:     <trID>
S:       <clTRID>a-client-reference</clTRID>
S:       <svTRID>tld-00000001</svTRID>
S:     </trID>
S:   </response>
S: </epp>
```