

Sample XML Commands

```
<?xml version='1.0' encoding='UTF-8'?>
<epp xmlns='urn:ietf:params:xml:ns:epp-1.0'
xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
xsi:schemaLocation='urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd'>
  <greeting>
    <svID>OpenXRS EPP Server Build: 1.0.9.11724</svID>
    <svDate>2011-10-27T13:38:50.0Z</svDate>
    <svcMenu>
      <version>1.0</version>
      <lang>en-US</lang>
      <objURI>urn:ietf:params:xml:ns:domain-1.0</objURI>
      <objURI>urn:ietf:params:xml:ns:host-1.0</objURI>
      <objURI>urn:ietf:params:xml:ns:contact-1.0</objURI>
      <svcExtension>
        <extURI>urn:afiliias:params:xml:ns:oxrs-1.1</extURI>
        <extURI>urn:ietf:params:xml:ns:rgp-1.0</extURI>
        <extURI>urn:afiliias:params:xml:ns:idn-1.1</extURI>
        <extURI>urn:afiliias:params:xml:ns:bulk-1.1</extURI>
        <extURI>urn:afiliias:params:xml:ns:mobi-1.1</extURI>
        <extURI>urn:afiliias:params:xml:ns:trademark-1.0</extURI>
      </svcExtension>
    </svcMenu>
    <dcP>
      <access>
        <personal/>
      </access>
      <statement>
        <purpose>
          <admin/>
          <contact/>
          <other/>
          <prov/>
        </purpose>
        <recipient>
          <ours>
            <recDesc>Afiliias</recDesc>
          </ours>
          <public/>
          <unrelated/>
        </recipient>
        <retention>
          <business/>
        </retention>
      </statement>
      <expiry>
        <relative>P10Y0M0DT0H0M0.0S</relative>
      </expiry>
    </dcP>
  </greeting>
```

Greeting

```
<?xml version='1.0' encoding='UTF-8'?>
<epp xmlns='urn:ietf:params:xml:ns:epp-1.0'
xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
xsi:schemaLocation='urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd'>
  <response>
    <result code='1000'>
      <msg lang='en-US'>Command completed successfully</msg>
    </result>
    <trID>
      <svTRID>SRO-1319722730359</svTRID>
    </trID>
  </response>
  <svcs>
    <objURI>urn:ietf:params:xml:ns:domain-1.0</objURI>
    <objURI>urn:ietf:params:xml:ns:host-1.0</objURI>
    <objURI>urn:ietf:params:xml:ns:contact-1.0</objURI>
  </svcs>
</login>
</command>
```

Login

```
<?xml version='1.0' encoding='UTF-8'?>
<epp xmlns='urn:ietf:params:xml:ns:epp-1.0'
xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
xsi:schemaLocation='urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd'>
  <response>
    <result code='1500'>
      <msg lang='en-US'>Command completed successfully; ending session</msg>
    </result>
    <trID>
      <svTRID>SRO-1319723264189</svTRID>
    </trID>
  </response>
```

Logout

```
<?xml version='1.0' encoding='UTF-8'?>
<epp xmlns='urn:ietf:params:xml:ns:epp-1.0'
xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
xsi:schemaLocation='urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd'>
  <response>
    <result code='1000'>
      <msg lang='en-US'>Command completed successfully</msg>
    </result>
    <resData>
      <domain:creData xmlns:domain='urn:ietf:params:xml:ns:domain-1.0'
xsi:schemaLocation='urn:ietf:params:xml:ns:domain-1.0 domain-1.0.xsd'>
        <domain:name>samplename.info</domain:name>
        <domain:crDate>2011-10-27T13:47:38.0Z</domain:crDate>
        <domain:exDate>2013-10-27T13:47:38.0Z</domain:exDate>
      </domain:creData>
    </resData>
    <trID>
      <svTRID>SRW-152283671</svTRID>
    </trID>
  </response>
</epp>
```

DomainCreate

```
<?xml version='1.0' encoding='UTF-8'?>
<epp xmlns='urn:ietf:params:xml:ns:epp-1.0'
xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
xsi:schemaLocation='urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd'>
  <response>
    <result code='1000'>
      <msg lang='en-US'>Command completed successfully</msg>
    </result>
    <resData>
      <contact:chkData xmlns:contact='urn:ietf:params:xml:ns:contact-1.0'
xsi:schemaLocation='urn:ietf:params:xml:ns:contact-1.0 contact-1.0.xsd'>
        <contact:cd>
          <contact:id avail='0'>C100</contact:id>
        </contact:cd>
      </contact:chkData>
    </resData>
    <trID>
      <svTRID>SRO-1319727044793</svTRID>
    </trID>
  </response>
</epp>
```

ContactCheck

```
<?xml version='1.0' encoding='UTF-8'?>
<epp xmlns='urn:ietf:params:xml:ns:epp-1.0'
xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
xsi:schemaLocation='urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd'>
  <response>
    <result code='1000'>
      <msg lang='en-US'>Command completed successfully</msg>
    </result>
    <trID>
      <svTRID>SRW-152290188</svTRID>
    </trID>
  </response>
  <host:rem></host:rem>
  </host:update>
</update>
</command>
```

HostUpdate