

Q25_XMLSchemaTCIDomain: XML-Schema "tci-domain-ext-1.0"

```
<?xml version="1.0" encoding="UTF-8"?>
<schema
  targetNamespace="http://www.tcinet.ru/epp/tci-domain-ext-1.0"
  xmlns:domExt=" http://www.tcinet.ru/epp/tci-domain-ext-1.0"
  xmlns:domain="urn:ietf:params:xml:ns:domain-1.0"
  xmlns="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">

  <annotation>
    <documentation>
      Extensible Provisioning Protocol v1.0
      domain extentions provisioning schema.
    </documentation>
  </annotation>

  <!--
  Child elements found in EPP commands.
  -->
  <element name="create" type="domExt:createType"/>
  <element name="update" type="domExt:updateType"/>

  <!--
  Child elements of the <create> command.
  -->
  <complexType name="createType">
    <sequence>
      <element name="description" type="domExt:descType"/>
    </sequence>
  </complexType>

  <simpleType name="descType">
    <restriction base="normalizedString">
      <maxLength value="1024"/>
    </restriction>
  </simpleType>

  <!--
  Child elements of the <update> command.
  -->
  <complexType name="updateType">
    <sequence>
      <element name="chg" type="domExt:chgType" />
    </sequence>
```

```
</complexType>
```

```
<!--
```

```
Data elements that can be changed.
```

```
-->
```

```
<complexType name="chgType">
```

```
  <sequence>
```

```
    <element name="description" type="domExt:descType"/>
```

```
  </sequence>
```

```
</complexType>
```

```
<!--
```

```
Child response elements.
```

```
-->
```

```
<element name="infData" type="domExt:createType"/>
```

```
</schema>
```